## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBAR	.IO
---------------------------------------	-----

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LA13-02023

Type	of light	source:
------	----------	---------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

		Froduct parar	ileters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
· · · · · · · · · · · · · · · · · · ·	mption in on- 00 h), rounded st integer	17	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone arrow cone (90º)	1 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	17,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen- sions without	Height Width	80 80	Spectral power distribution in the	See image in last page
separate con- trol gear, light- ing control	Depth	148	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	115
		Chromaticity coordinates (x and y)	0,313 0,337
Parameters for LED and OLED I	ight sources:		
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,94		
Parameters for LED and OLED r	nains light sources:		
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	5
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;