## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or trade m	nark:	LAMBARIO
------------	------	------------	-------	----------

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LA38-00820

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neares	00 h), rounded	8	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		850 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P <sub>on</sub> ), expressed in W		8,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	105	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equiva	lent power <sup>(a)</sup>	Yes	If yes, equivalent power (W)	60	
			Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED light sources:					
R9 colour rende	ring index value	19	Survival factor	0,90	
the lumen maintenance factor		0,96			
Parameters for	LED and OLED m	ains light sources:			
displacement fa	ctor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6	
replaces a flu	LED light source uorescent light integrated balar wattage.	Yes <sup>(b)</sup>	If yes then replace- ment claim (W)	60	
Flicker metric (F	Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;