## **Product Information Sheet**

ing control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

commission D sources	ELEGATED REGUI	LATION (EU) 2019/2	015 with regard to ener	gy labelling of light
Supplier's name	or trade mark:	LAMBARIO		
Supplier's addre	ess: LAMBARIO L	TD, Poljkovnik Dran	gov 2, 2850 Blagoevgrad	d, BG
Model identifie	r: LG36-0109			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		-		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		Yes		
Anti-glare shield:		No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone		509 in Sphere (360°)	Energy efficiency class  Correlated colour temperature, rounded to the nearest 100 K, or the	400
(120º) or in a narrow cone (90º)			range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power (P <sub>on</sub> ), expressed in W		4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimensions without separate control gear, light-	Height Width Depth	100 100 90	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,380			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;