Product Information Sheet

ing control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| commission D sources | ELEGATED REGUI | -ATION (EU) 2019/2 | 015 with regard to ener | gy labelling of light |
|---|------------------|---------------------------------|---|-----------------------|
| Supplier's name | e or trade mark: | LAMBARIO | | |
| Supplier's addre | ess: LAMBARIO L | TD, Poljkovnik Dran | gov 2, 2850 Blagoevgrad | d, BG |
| Model identifie | r: LN23-00630 | | | |
| Type of light so | urce: | | | |
| Lighting technology used: | | LED | Non-directional or directional: | NDLS |
| Light source cap-type | | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | | No | Envelope: | - |
| High luminance light source: | | No | | |
| Anti-glare shield: | | No | Dimmable: | No |
| | | Product para | meters | |
| Parameter | | Value | Parameter | Value |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer Useful luminous flux (фuse), in- dicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 3 225 in Wide cone (120°) | Energy efficiency class Correlated colour temperature, rounded to the nearest 100 K, or the | G 6 400 |
| On-mode power (P _{on}), ex- | | 3,0 | range of correlated colour temperatures, rounded to the nearest 100 K, that can be set Standby power (P _{sb}), | 0,00 |
| pressed in W | | | expressed in W and rounded to the second decimal | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 55 | Spectral power dis- | See image |
| sions without separate con- trol gear, light- | Width Depth | 70 70 | tribution in the range 250 nm to 800 nm, at full-load | in last page |

| parts and non- lighting con- trol parts, if any (millime- | | | | | | |
|---|------|--|----------------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordinates (x and y) | 0,316 0,343 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 42 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,96 | | | | | |
| Parameters for LED and OLED mains light sources: | | | | | | |
| displacement factor (cos φ1) | 0,50 | Colour consistency in McAdam ellipses | 6 | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replace- ment claim (W) | - | | | |
| Flicker metric (Pst LM) | 1,0 | Stroboscopic effect metric (SVM) | 0,4 | | | |

(a)'-': not applicable; (b)'-': not applicable;

