## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or trade mar | k: Lambario |
|------------------------------|-------------|
|------------------------------|-------------|

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LP01-31210

| Type of light source: | Type | of light | source: |
|-----------------------|------|----------|---------|
|-----------------------|------|----------|---------|

| LED  | Non-directional or directional: | NDLS   |
|------|---------------------------------|--|
| -    |                                 |  |
|      |                                 |  |
| NMLS | Connected light source (CLS):   | No   |
| No   | Envelope:                       | -  |
| No   |                                 |  |
| No   | Dimmable:                       | No   |
|      | NMLS No No                      | NMLS Connected light source (CLS):  No Envelope:  No |

## **Product parameters**

| Froduct parameters                                |  |                           |  |              |
|---|--|---------------------------|--|--------------|
| Parameter   |  | Value                     | Parameter  | Value        |
| General product parameters:                       |  |                           |  |              |
|   | mption in on-<br>00 h), rounded<br>st integer                                    | 12                        | Energy efficiency class  | F            |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), in-<br>ers to the flux in<br>, in a wide cone<br>arrow cone (90º) | 1 200 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-  | 11,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |
| (P <sub>net</sub> ) for CLS, 6                    | tandby power expressed in W the second dec-                                      | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |
| Outer dimen-                                      | Height   | 175                       | Spectral power dis-  | See image    |
| sions without                                     | Width  | 155                       | tribution in the   | in last page |
| separate con-<br>trol gear, light-<br>ing control | Depth  | 21                        | range 250 nm to 800<br>nm, at full-load  |              |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |
|--|------|------------------------------|-------|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |
|  |      | Chromaticity coordi-         | 0,365 |
|  |      | nates (x and y)              | 0,360 |
| Parameters for LED and OLED light sources:                                 |      |                              |       |
| R9 colour rendering index value  | -    | Survival factor              | 0,90  |
| the lumen maintenance factor   | 0,96 |                              |       |

(a)'-': not applicable; (b)'-': not applicable;