## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

0

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LP03-32410

Type of light sour	Type	of li	ght	sourc	e:
--------------------	------	-------	-----	-------	----

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product pa	arameters	
Darameter	Value	Darameter	Value

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 00 h), rounded st integer	24	Energy efficiency class	E
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	2 450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	20,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	300	Spectral power dis-	See image
sions without	Width	300	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	31	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,365	
		nates (x and y)	0,360	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;