Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Suppl | ier's | name | or | trade | mark: | LAMBARIO | |
|-------|-------|------|----|-------|-------|----------|--|
|-------|-------|------|----|-------|-------|----------|--|

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 3, 2850 Blagoevgrad, BG

Model identifier: LP04-32400

| Τv | pe | of | light | soui | ce: |
|-----|----|----|-------|------|-----|
| . , | P- | • | | | ··· |

| Parameter | Value | Parameter | Value | | |
|---|-------|------------------------------|---------|--|--|
| Product parameters | | | | | |
| Anti-glare shield: | No | Dimmable: | No | | |
| High luminance light source: | No | | | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| Mains or non-mains: | NMLS | Connected lig source (CLS): | ht No | | |
| Light source cap-type (or other electric interface) | - | | | | |
| Lighting technology used: | LED | Non-directional directional: | or NDLS | | |

| Product parameters | | | | | | |
|---|---|---------------------------|--|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consur mode (kWh/10 up to the neare | 00 h), rounded | 24 | Energy efficiency class | E | | |
| dicating if it refe a sphere (360º) | s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º) | 2 450 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode pow pressed in W | ver (P _{on}), ex- | 20,5 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | | |
| Outer dimen- | Height | 300 | Spectral power dis- | See image | | |
| sions without | Width | 300 | tribution in the | in last page | | |
| separate con- trol gear, light- ing control | Depth | 31 | range 250 nm to 800 nm, at full-load | | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | |
|--|------|------------------------------|-------|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | |
| | | Chromaticity coordi- | 0,433 | | |
| | | nates (x and y) | 0,403 | | |
| Parameters for LED and OLED light sources: | | | | | |
| R9 colour rendering index value | - | Survival factor | 0,90 | | |
| the lumen maintenance factor | 0,96 | | | | |

(a)'-': not applicable; (b)'-': not applicable;