Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO					

Supplier's address:	LAMBARIO LTD	, Poljkovnik	Drangov 2	, 2850 Bl	lagoevgrad, I	BG
---------------------	--------------	--------------	-----------	-----------	---------------	----

Mode	l identifier:	LP15-03110
------	---------------	------------

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No
Duradicat page at an			

Product parameters

Troduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	nption in on- 00 h), rounded st integer	40	Energy efficiency class	D	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	5 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode pow pressed in W	ver (P _{on}), ex-	37,2	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimensions without separate con-	Height Width	1 195 24	Spectral power distribution in the range 250 nm to 800	See image in last page	
trol gear, light- ing control	Depth	9	nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,380	
		nates (x and y)	0,380	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;