## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO
Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier:	LP15-06610
-------------------	------------

Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

## Product parameters

	1 Todact paral		
	Value	Parameter	Value
	General product p	arameters:	
ption in on- 00 h), rounded t integer	40	Energy efficiency class	D
flux (фuse), in- rs to the flux in in a wide cone row cone (90º)	5 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
er (P <sub>on</sub> ), ex-	35,4	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
andby power xpressed in W he second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Height Width Depth	595 595 -	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	integer flux (φuse), integer flux (φuse), integer flux (φuse), integer flux in in a wide cone flux (90º)  frow cone (90º)  from (Pon), extended from power from powe	General product p  ption in on- 0 h), rounded t integer  flux (фuse), in- rs to the flux in in a wide cone row cone (90º)  er (Pon), ex-  andby power expressed in W the second dec-  Height  5000 in Sphere (360°)  - 35,4	ption in on- 0 h), rounded tinteger  flux (фuse), in- rs to the flux in in a wide cone row cone (90°)  er (Pon), ex-  and by power expressed in W he second decimal  mindby power expressed in W he second decimal  mindby power type service of the product parameters:  Energy efficiency class  Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set  Standby power (Psb), expressed in W and rounded to the second decimal  Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set  Height 595  Width 595  Depth -

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,380
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;