Product Information Sheet

Outer dimen-

sions without

separate con-

trol gear, light-

control

ing

Height

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG Model identifier: LS02-00304									
						Type of light source:			
						Lighting technology used:	LED	Non-directional or directional:	NDLS
						Light source cap-type	-		
(or other electric interface)									
Mains or non-mains:	NMLS	Connected light source (CLS):	No						
Colour-tuneable light source:	No	Envelope:	-						
High luminance light source:	No								
Anti-glare shield:	No	Dimmable:	No						
	Product para	meters							
Parameter	Value	Parameter	Value						
General product parameters:									
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	F						
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000						
On-mode power (P _{on}), expressed in W	20,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00						
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val-	80						

1

10

1 000

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

tribution

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,373	
		nates (x and y)	0,371	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	11	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;