Product Information Sheet

Networked standby

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

power

80

580

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

	i D, Poljkovnik Dran	gov 2, 2850 Blagoevgrac	i Petric, BG
Model identifier: LT02-00630			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	LED		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 000 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500
On-mode power (P _{on}), ex- pressed in W	17,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

the

tribution

Page	1	/	2

80

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,341			
		nates (x and y)	0,336			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	6	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;