Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO						
Supplier's address: LAMBARIO L	TD, Poljkovnik Drang	gov 2, 2850 Blagoevgrad	Petric, BG			
Model identifier: LT05-01230						
Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	-					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	Yes					
Anti-glare shield:	No	Dimmable:	No			
	Product para	meters				
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	36	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	4 100 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the	6 500			

a sphere (360º), (120º) or in a na	in a wide cone	conc (120)	rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode pow pressed in W	rer (P _{on}), ex-	35,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked st (P _{net}) for CLS, e and rounded to imal	-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	66	Spectral power dis-	See image
sions without	Width	1 200	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	58	range 250 nm to 800 nm, at full-load	
·				Page 1 / 2

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,313			
		nates (x and y)	0,317			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;