## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad Blagoevgrad Petric,

BG

Model identifier: LT10-01510

Type	of lig	ht s	ource:
------	--------	------	--------

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type			
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
	mption in on- 00 h), rounded st integer	48	Energy efficiency class	D		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		7 100 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P <sub>on</sub> ), expressed in W		47,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	1 477	Spectral power dis-	See image		
sions without	Width	60	tribution in the	in last page		
separate con- trol gear, light-	Depth	12	range 250 nm to 800 nm, at full-load			

ing control parts and non-lighting control parts, if any (millimetre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	14	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

