## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

## Model identifier: LT60-01010

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	-					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 00 h), rounded st integer	10	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 010 in Wide cone (120°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	4 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	10,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
( $P_{net}$ ) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	70		
Outer dimen- sions without separate con- trol gear, light- ing control	Height	90	Spectral power dis-	See image		
	Width	86	tribution in the range 250 nm to 800 nm, at full-load	in last page		
	Depth	27		Page 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,380 0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	_			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;