Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LAMBARIO		
Supplier's address: LAMBARIO L	TD, Poljkovnik Drang	gov 2, 2850 Poljkovnik D	rangov, BG
Model identifier: LA07-00723			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
	Product parar	neters	
Parameter	Value	Parameter	Value
	General product p	arameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	F
Useful luminous flux (duse) in-	806 in	Correlated colour	6.400

General product parameters:							
	nption in on- 00 h), rounded st integer	8	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 400			
On-mode pov pressed in W	ver (P _{on}), ex-	8,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P _{net}) for CLS, (candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	88	Spectral power dis-	See image			
sions without	Width	45	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	45	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,313 0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9 0	Survival factor	0,90			
the lumen maintenance factor	0,94					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	5			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;