Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO Supplier's address: LAMBARIO LTD, www.lambario.com 2, 2850 www.lambario.com, BG						
Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	E14					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light	No			

Light source cap-type (or other electric interface) Mains or non-mains: MLS Connected light No source (CLS): Colour-tuneable light source: No Envelope: High luminance light source: No Dimmable: No Product parameters

I ngn rannnance							
Anti-glare shield	d:	No	Dimmable:	No			
Product parameters							
Parameter		Value	Parameter	Value			
General product parameters:							
	nption in on- 00 h), rounded st integer	6	Energy efficiency class	F			
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone errow cone (90º)	540 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode pow pressed in W	ver (P _{on}), ex-	6,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80			
Outer dimen-	Height	100	Spectral power dis-	See image			
sions without	Width	37	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	37	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	44			
		Chromaticity coordinates (x and y)	0,430 0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,51	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;