## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LD31-03000

## Type of light source:

| Lighting technology used:     | LED  | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|------|---------------------------------|------|--|--|--|
| Light source cap-type         | -    |                                 |      |  |  |  |
| (or other electric interface) |      |                                 |      |  |  |  |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |  |  |  |
| Colour-tuneable light source: | No   | Envelope:                       | -    |  |  |  |
| High luminance light source:  | Yes  |                                 |      |  |  |  |
| Anti-glare shield:            | No   | Dimmable:                       | No   |  |  |  |
| Product parameters            |      |                                 |      |  |  |  |

| rioudet parameters   |   |                           |  |              |  |  |
|--|---|---------------------------|--|--------------|--|--|
| Parameter  |   | Value                     | Parameter  | Value        |  |  |
| General product parameters:  |   |                           |  |              |  |  |
| 0,   | nption in on-<br>00 h), rounded<br>st integer                                   | 30                        | Energy efficiency<br>class   | F            |  |  |
| dicating if it refe<br>a sphere (360°)                             | s flux (φuse), in-<br>ers to the flux in<br>, in a wide cone<br>rrow cone (90º) | 2 600 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 3 000        |  |  |
| On-mode pow<br>pressed in W  | ver (P <sub>on</sub> ), ex-   | 27,9                      | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | -            |  |  |
| (P <sub>net</sub> ) for CLS, e                                     | andby power<br>expressed in W<br>the second dec-                                | -                         | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |
| Outer dimen-   | Height  | 180                       | Spectral power dis-  | See image    |  |  |
| sions without<br>separate con-<br>trol gear, light-<br>ing control | Width<br>Depth  | -                         | tribution in the<br>range 250 nm to 800<br>nm, at full-load  | in last page |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |      |                              |       |  |  |  |
|--|------|------------------------------|-------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>                                   | -    | If yes, equivalent power (W) | -     |  |  |  |
|  |      | Chromaticity coordi-         | 0,440 |  |  |  |
|  |      | nates (x and y)              | 0,403 |  |  |  |
| Parameters for LED and OLED light sources:                                 |      |                              |       |  |  |  |
| R9 colour rendering index value  | 3    | Survival factor              | 0,90  |  |  |  |
| the lumen maintenance factor   | 0,96 |                              |       |  |  |  |
| (a)  |      |                              |       |  |  |  |

(a)'-' : not applicable;

(b)'-' : not applicable;