## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad Blagoevgrad Petric,

BG

Mode	l identifier:	LDC01-08
------	---------------	----------

IVI	~~		anı	,	<b>111</b> 1	$\boldsymbol{c}$
IVL			211		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Typ		,	о			•••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

## **Product parameters**

Product parameters				
Parameter		Value	Parameter	Value
General product parameters:				
<u> </u>	nption in on- 00 h), rounded st integer	26	Energy efficiency class	E
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	27005500
On-mode power (P <sub>on</sub> ), expressed in W		26,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	45	Spectral power dis-	See image
sions without	Width	510	tribution in the	in last page
separate con- trol gear, light-	Depth	510	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,457
		nates (x and y)	0,412
Parameters for LED and OLED light sources:			
R9 colour rendering index value 1		Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;