Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name | or trade mark: | LAMBARIO |
|-----------------|----------------|----------|
|-----------------|----------------|----------|

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LP01-32400

| Type | of I | ight | sour | ce: |
|------|--------------|-------|------|-----|
| IVE | U I I | ISIIL | JUUI | ··· |

| Lighting technology used: | LED | Non-directional or directional: | NDLS | |
|-------------------------------|------|---------------------------------|------|--|
| Light source cap-type | - | | | |
| (or other electric interface) | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | |
| Colour-tuneable light source: | No | Envelope: | - | |
| High luminance light source: | No | | | |
| Anti-glare shield: | No | Dimmable: | No | |
| Duradicat negreeature | | | | |

Product parameters

| Froduct parameters | | | | |
|---|--|---------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | General product parameters: | | | |
| | mption in on- 00 h), rounded st integer | 24 | Energy efficiency class | E |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º) | 2 450 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 20,5 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | candby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 |
| Outer dimen- | Height | 300 | Spectral power dis- | See image |
| sions without | Width | 285 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 21 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|--|------|------------------------------|-------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordi- | 0,433 |
| | | nates (x and y) | 0,403 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | - | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |

(a)'-': not applicable; (b)'-': not applicable;