## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

## Model identifier: LS01-00403

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	-				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	No		
Product parameters					

	FIGUUCE parai				
	Value	Parameter	Value		
General product parameters:					
nption in on- 00 h), rounded st integer	12	Energy efficiency class	G		
s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	750 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	6 500		
ver (P <sub>on</sub> ), ex-	12,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Height	3	Spectral power dis-	See image		
Width Depth	10 1 000	tribution in the range 250 nm to 800 nm, at full-load	in last page		
	00 h), rounded st integer s flux (¢use), in- ers to the flux in , in a wide cone rrow cone (90º) ver (Pon), ex- candby power expressed in W the second dec- Height Width	ValueGeneral product pnption in on- 00 h), rounded st integera flux (\$\phi\$use), in- ers to the flux in , in a wide cone rrow cone (\$90\$)ver (\$P_{on}\$), ex- expressed in \$W\$ver (\$P_{on}\$), ex- expressed in \$W\$Height3 Width	ValueParameterGeneral product parameters:nption in on- 00 h), rounded st integer12Energy efficiency classa flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90°)750 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setver (Pon), ex- expressed in W the second dec-12,0Standby power (Psb), expressed in W the second dec-Height3Spectral power dis- tribution in the range 250 nm to 800		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,301		
		nates (x and y)	0,322		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	8	Survival factor	0,90		
the lumen maintenance factor	0,96				
(a)	÷				

(a)'-' : not applicable;

(b)'-' : not applicable;