Product Information Sheet

sions without

separate con-

trol gear, light-

control

ing

Width

Depth

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG Model identifier: LS03-00450											
							Type of light source	e:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
							Light source cap-typ	oe	-		
(or other electric in	terface)										
Mains or non-mains	s:	NMLS	Connected light source (CLS):	No							
Colour-tuneable lig	ht source:	No	Envelope:	-							
High luminance light source:		No									
Anti-glare shield:		No	Dimmable:	No							
		Product para	meters								
Parameter		Value	Parameter	Value							
		General product p	arameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	G							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		700 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000							
On-mode power (P _{on}), expressed in W		8,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80							
Outer dimen- He	eight	1	Spectral power dis-	See image							

tribution

8

1 000

the

in

range 250 nm to 800

nm, at full-load

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,382			
		nates (x and y)	0,383			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;