## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or | r trade mark: | LAMBARIO |
|--------------------|---------------|----------|
|--------------------|---------------|----------|

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG

Model identifier: LT63-09112

| I V DC OI IISIIL JOUI CC | Type | of lig | tht s | ource: |
|--------------------------|------|--------|-------|--------|
|--------------------------|------|--------|-------|--------|

| Lighting technology used:     | LED             | Non-directional or directional: | NDLS |
|-------------------------------|-----------------|---------------------------------|------|
| Light source cap-type         | -               |                                 |      |
| (or other electric interface) |                 |                                 |      |
| Mains or non-mains:           | MLS             | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No              | Envelope:                       | -    |
| High luminance light source:  | Yes             |                                 |      |
| Anti-glare shield:            | No              | Dimmable:                       | No   |
|                               | Dunalisat innun |                                 |      |

## **Product parameters**

| Froduct parameters                                |   |                            |  |              |
|---|---|----------------------------|--|--------------|
| Parameter   |   | Value                      | Parameter  | Value        |
|   | General product parameters:   |                            |  |              |
|   | mption in on-<br>00 h), rounded<br>st integer                         | 100                        | Energy efficiency class  | E            |
| dicating if it refe<br>a sphere (360º)            | s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º) | 12 225 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000        |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-   | 98,9                       | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |
| (P <sub>net</sub> ) for CLS, 6                    | candby power expressed in W the second dec-                           | -                          | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |
| Outer dimen-                                      | Height  | 318                        | Spectral power dis-  | See image    |
| sions without                                     | Width   | 225                        | tribution in the   | in last page |
| separate con-<br>trol gear, light-<br>ing control | Depth   | 40                         | range 250 nm to 800<br>nm, at full-load  |              |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-  |                      |  |       |
|---|----------------------|--|-------|
| tre)  |                      |  |       |
| Claim of equivalent power <sup>(a)</sup>  | -                    | If yes, equivalent power (W)           | -     |
|   |                      | Chromaticity coordi-                   | 0,385 |
|   |                      | nates (x and y)                        | 0,382 |
| Parameters for LED and OLED I   | ight sources:        |  |       |
| R9 colour rendering index value   | 9 0                  | Survival factor                        | 1,00  |
| the lumen maintenance factor  | 0,96                 |  |       |
| Parameters for LED and OLED r   | nains light sources: |  |       |
| displacement factor (cos φ1)  | 0,90                 | Colour consistency in McAdam ellipses  | 6     |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | :                    | If yes then replace-<br>ment claim (W) | -     |
| Flicker metric (Pst LM)   | 1,0                  | Stroboscopic effect metric (SVM)       | 0,9   |

(a)'-': not applicable; (b)'-': not applicable;