Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LAMBARIO		
Supplier's address: LAMBARIO I		gov 2, 2850 Blagoevgrac	l, BG
Model identifier: MLL01-21			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	20	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in	1 955 in Sphere (360°)	Correlated colour temperature,	3 000

General product parameters:						
<u> </u>	nption in on- 00 h), rounded st integer	20	Energy efficiency class	F		
dicating if it refe a sphere (360º) (120º) or in a na	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 955 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P _{on}), ex-	19,1	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	58	Spectral power dis-	See image		
sions without	Width	58	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	152	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,421			
		nates (x and y)	0,395			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	62	Survival factor	0,90			
the lumen maintenance factor	0,96					

(a)'-': not applicable; (b)'-': not applicable;