Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad Blagoevgrad Petric,

BG

| Mode | l identifier: | MLL01-26 |
|------|---------------|----------|
|------|---------------|----------|

| Tν | ne | οf | lighi | t sai | urce: |
|----|----|-----|-------|-------|-------|
| ·у | PC | VI. | ugu | . 30 | uice. |

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|------|---------------------------------|------|
| Light source cap-type | - | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

Product parameters

| Product parameters | | | | | |
|---|--|---------------------------|--|--------------|--|
| Parameter | | Value | Parameter | Value | |
| General product parameters: | | | | | |
| <u> </u> | mption in on- 00 h), rounded st integer | 18 | Energy efficiency class | F | |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º) | 1 809 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 4 000 | |
| On-mode power (P _{on}), expressed in W | | 18,7 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 80 | |
| Outer dimen- | Height | 41 | Spectral power dis- | See image | |
| sions without | Width | 25 | tribution in the | in last page | |
| separate con- trol gear, light- | Depth | 42 | range 250 nm to 800 nm, at full-load | | |

| ing control parts and non-lighting control parts, if any (millimetre) | | | |
|---|------|------------------------------|-------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordi- | 0,380 |
| | | nates (x and y) | 0,380 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value - | | Survival factor | 0,90 |
| the lumen maintenance factor | 0,96 | | |

(a)'-': not applicable; (b)'-': not applicable;