Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad Blagoevgrad Petric,

BG

Model	identifier:	MLL01-37
-------	-------------	----------

IVI	~~		anı	,	111 1	\boldsymbol{c}
IVL			211		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Typ		,	о			•••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consur mode (kWh/10 up to the neare	00 h), rounded	12	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), iners to the flux in , in a wide cone arrow cone (90º)	1 223 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P _{on}), expressed in W		12,1	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	215	Spectral power dis-	See image	
sions without	Width	25	tribution in the	in last page	
separate con- trol gear, light-	Depth	120	range 250 nm to 800 nm, at full-load		

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,380
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value -		Survival factor	0,90
the lumen maintenance factor	0,96		

(a)'-': not applicable; (b)'-': not applicable;