## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad Blagoevgrad Petric,

BG

AboM	lidentifier:	MH101-53
MUUGE	iuenunei.	INITEDT-23

т.,	nn	Λf	امزا	h+	50		co.
ıу	hΕ	UI	IIBI	IΙL	30	u	ce:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	mption in on- 00 h), rounded st integer	12	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 367 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P <sub>on</sub> ), ex- pressed in W		12,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	115	Spectral power dis-	See image	
sions without	Width	45	tribution in the	in last page	
separate con- trol gear, light-	Depth	105	range 250 nm to 800 nm, at full-load		

ing control parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power <sup>(c</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,444	
		nates (x and y)	0,413	
Parameters for LED and OLED light sources:				
R9 colour rendering index value -		Survival factor	0,90	
the lumen maintenance fac	tor 0,94			

(a)'-': not applicable; (b)'-': not applicable;