## **Product Information Sheet**

ing control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

commission D sources	ELEGATED REGUI	-ATION (EU) 2019/2	015 with regard to ener	gy labelling of light
Supplier's name	e or trade mark:	LAMBARIO		
Supplier's addre	ess: LAMBARIO L	TD, Poljkovnik Dran	gov 2, 2850 Blagoevgrad	d, BG
Model identifie	r: PL05-00700			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		-		
(or other electric interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		Yes		
Anti-glare shield:		No	Dimmable:	No
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	F
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P <sub>on</sub> ), ex- pressed in W		7,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81
Outer dimensions without separate control gear, light-	Height Width Depth	25 116 116	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,440 0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	2	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED m	ains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;