Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	LAMBARIO		
Supplier's address: LAMBARIO L	TD, Poljkovnik Dran	gov 2, 2850 Blagoevgrad	l, BG
Model identifier: PL05-01500			
Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	Yes		
Anti-glare shield:	No	Dimmable:	No
	Product para	meters	
Parameter	Value	Parameter	Value
	General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	15	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000

			atures, rounded to the nearest 100 K, that can be set	
On-mode pow pressed in W	ver (P _{on}), ex-	15,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	81
Outer dimen-	Height	26	Spectral power dis-	See image
sions without	Width	176	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	176	range 250 nm to 800 nm, at full-load	
				Page 1 /

parts and non- lighting con- trol parts, if any (millime- tre)							
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-				
		Chromaticity coordinates (x and y)	0,440 0,403				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	1	Survival factor	0,90				
the lumen maintenance factor	0,96						
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	5				
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-				
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4				

(a)'-': not applicable; (b)'-': not applicable;