## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO				
Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG				

Model identifier:	PL06-01500
-------------------	------------

Type	٥f	liaht	SOLI	rco.
IVDE	UI	IIKIIL	SUU	ıce.

LED	Non-directional or directional:	NDLS
-		
MLS	Connected light source (CLS):	No
No	Envelope:	-
Yes		
No	Dimmable:	No
	- MLS No Yes	directional:  -  MLS Connected light source (CLS):  No Envelope:  Yes

## **Product parameters**

Parameter		Value	Parameter	Value	
	General product parameters:				
٠,	nption in on- 00 h), rounded st integer	15	Energy efficiency class	F	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	1 600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	15,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81	
Outer dimensions without	Height	28	Spectral power distribution in the	See image	
	Width	176		in last page	
separate con- trol gear, light- ing control	Depth	176	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED lig	ght sources:			
R9 colour rendering index value	2	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	4,0	

(a)'-': not applicable; (b)'-': not applicable;