Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO

Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Poljkovnik Drangov, BG

Model identifier: PL06-02500

Type of light source:

LED	Non-directional or directional:	NDLS
-		
MLS	Connected light source (CLS):	No
No	Envelope:	-
Yes		
No	Dimmable:	No
	- MLS No Yes	directional:-directional:-Connected light source (CLS):NoEnvelope:YesImage: Connected light source (CLS):

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	nption in on- 00 h), rounded st integer	25	Energy efficiency class	F		
dicating if it refe a sphere (360 ^o)	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	2 400 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 000		
On-mode pow pressed in W	ver (P _{on}), ex-	23,8	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
(P _{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	28	Spectral power dis-	See image		
sions without	Width	294	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	294	range 250 nm to 800 nm, at full-load	Page 1 /		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	0,440 0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;