Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO			
Supplier's address: LAMBARIO LTD, Poljkovnik Drangov 2, 2850 Blagoevgrad, BG			

Model identifier:	PL08-02010
-------------------	------------

_	•			
Ivpe	OΤ	light	source	

Anti-glare shield:	No	Dimmable:	No
High luminance light source:	Yes		
Colour-tuneable light source:	No	Envelope:	-
Mains or non-mains:	MLS	Connected light source (CLS):	No
(or other electric interface)			
Light source cap-type	-		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Product parameters

		1 Todact parar		I
Parameter		Value	Parameter	Value
		General product p	arameters:	
<u> </u>	mption in on- 00 h), rounded st integer	20	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	2 050 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	19,6	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	32	Spectral power dis-	See image
sions without	Width	223	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	230	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,380 0,380	
Parameters for LED and OLED lig	Parameters for LED and OLED light sources:			
R9 colour rendering index value	2	Survival factor	0,90	
the lumen maintenance factor	0,96			
Parameters for LED and OLED m	Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	5	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;