Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LAMBARIO						
Supplier's address: LAMBARIO L	TD, Poljkovnik Dran	gov 2, 2850 Blagoevgrad	l, BG			
Model identifier: PL08-02530 Type of light source:						
Light source cap-type	-					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	Yes					
Anti-glare shield:	No	Dimmable:	No			
	Product para	meters				
Parameter	Value	Parameter	Value			
	General product p	parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	25	Energy efficiency class	F			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	2 450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K,	6 400			

			the nearest 100 K, that can be set	
On-mode pow pressed in W	ver (P _{on}), ex-	24,4	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81
Outer dimen-	Height	32	Spectral power dis-	See image
sions without	Width	295	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	302	range 250 nm to 800 nm, at full-load	
1	1	,	•	Page 1 /

parts and non- lighting con- trol parts, if any (millime-						
tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,313			
		nates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	3	Survival factor	0,90			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;